



DY-SAAM 乘驾式空气辅助型常温标线机 Small Air Spray Road Marking Machine

- ◆1.Engine: Imported Honda 20 HP air-cooled gasoline engine.The fuel tank capacity is 50L.
- ◆2.Driving system: Imported oil pressurized continuously variable speed transmission system (HTS) with automatic brake device.The left and right back wheels are equipped with a differential speed gearing to ensure it to drive freely around the curve and change directions timely.Driving speed: 0-22km/h, maximum climbing capacity: 15° .
- ◆3.Air compressor: 1m³/min displacement piston air compressor with enough and stable pressurized air.
- ◆4.Paint tank: Equipped with single pressurized paint tank with hydraulic driven type stirring device; capacity: 200L.
- ◆5.Spray gun: Equipped with double pneumatic low pressure atomized air spray guns.The spray width is 100-450mm.

注:可选配DY-TT专用拖车,方便机器长途运输。

Remark:Optional for DY-TT trailer for long distance transportation



- ◆6.Available paint: Applying to cold solvent paint and water based paint.
- ◆7.Glass beads spraying system: Single equipped with pressurized 60L glass beads bin with a window.Single or double glass beads spraying guns can be equipped on the left or right that can freely adjust its pressure , flow rate and spray width to ensure the spraying glass beads firmer, evener and more economical.
- ◆8.Chassis: A firm welded, four-wheel structure with a 500mm inflatable pressure-proof wheel.The operators can operate the machine sitting on the left or right and use the hydraulic steering to freely control directions.The stable brake system makes the driving more secure.
- ◆9.Lighting and warning function: The originally equipped highlight headlamp makes the night marking operation more convenient.The warning lights can freely adjust its flicker frequency, greatly improving the marking operations' safety.
- ◆10.Electronic control system: Multiple marking standard control modes, realizing the micro-electronic intelligent control, and can adjust the standards according to the customers needs.
- ◆11.Guide rod: Can be freely adjusted to up, down, left or right.

- ◆1.引擎: 原装进口本田20HP空冷式汽油发动机,燃油箱容积50L。
- ◆2.驱动系统: 原装进口的带自动刹车装置且前进、后退及停止可灵便操作的油压式无级变速系统 (HTS)。左右后轮为差速式传动装置,弯道行驶及转向时更灵活。驱动速度0-22km/h,最大爬坡能力为15度。
- ◆3.空压机: 1m³/min排量活塞式气泵,气源量足压稳。
- ◆4.涂料罐: 单配加压式内置液压传动叶片式搅拌装置涂料罐,罐容量为200L。
- ◆5.喷涂枪: 双配新型气动低压雾化空气辅助式喷枪,喷涂幅度为100mm-450mm。
- ◆6.适用涂料: 适用于常温溶剂型、常温水性涂料的喷涂。
- ◆7.玻璃珠喷播系统: 单配60L加压式带视窗玻璃珠贮罐。左右单配可调压力、流量及喷幅的玻璃珠喷枪,确保喷珠更牢固、更均匀、更节省。
- ◆8.底盘: 坚固焊接框架,四轮结构,轮胎为充气式耐压工程轮,轮直径为500mm;操作员左侧或右侧乘坐式操作,操作员通过液压助力方向盘(可根据用户需要在左侧或右侧设置)控制转向自如;带稳定的刹车系统,行驶更安全。
- ◆9.照明与警示功能: 随机所配的高亮度照明灯,方便夜间标线作业。可自由调整闪烁频率的警示灯,大大提高了标线作业的安全性。
- ◆10.电子控制系统: 设置多种标线标准控制方式,实现了微电子智能控制,并可根据用户个性化需要任意调整线型。
- ◆11.导向杆: 抽拉式导向杆,上、下、左、右调整便利。
- ◆12.外形尺寸·整机重量: 3400mm(长)x2000mm(宽)x2400mm(高)·780kg。